

# Verlegeanleitung



easyloc Diele ohne integrierte Trittschalldämmung

**1**

18-23°C  
64-73°F

48h

**2**

**3**

DIN 18365, EN 1264  
CA 0,3 CM % CT 1,8 CM %

**4**

max. 2 mm / 1 m  
5/64 inch / 1 inch

**5**

max. 1,5 mm  
min. 150 kPa

**6**

max. 1,5 mm / 1/32 inch  
min. 150 kPa

**7**

18-23°C  
64-73°F

**8**

10 mm  
3/8 inch

> 50 cm  
20 inch

> 20 cm  
8 inch

**9**

**10**

max. 12 m  
max. 39 feet

**11**

max. 29°C  
84°F

**12**

10 mm  
3/8 inch

10 mm  
3/8 inch

**13**

**14**

max. 1 mm  
3/64 inch

max. 8 mm  
5/16 inch

**15**

min. 40 cm  
16 inch

**16**

min. 10 cm / 4 inch

90°

min. 10 cm / 4 inch

**17**

10 mm  
3/8 inch

**18**

**19**

10 mm  
3/8 inch

**20**

1 2

**21**

**22**

**23**

**24**

**25**

**26**

**27**

**28**

**29**

**30**

Written Installation Instructions -  
Professional Tips - Certificates